

# Package ‘rntp’

July 23, 2025

**Title** Wrapper for the National Bank of Poland API

**Version** 0.2.2

**Maintainer** Ryszard Szymanski <ryszard.szymanski@outlook.com>

**Description** Use the <<https://api.nbp.pl/>> API through R. Retrieve currency exchange rates and gold prices data published by the National Bank of Poland in form of convenient R objects.

**License** GPL-3

**BugReports** <https://github.com/szymanski/rntp/issues>

**Encoding** UTF-8

**Imports** curl, httr, jsonlite, utils

**Suggests** covr, httpptest, testthat (>= 2.1.0), knitr, rmarkdown, ggplot2

**RoxygenNote** 7.3.2

**VignetteBuilder** knitr

**URL** <https://github.com/szymanski/rntp>

**NeedsCompilation** no

**Author** Ryszard Szymanski [aut, cre]

**Repository** CRAN

**Date/Publication** 2025-03-23 20:40:02 UTC

## Contents

.goldprice_base_url . . . . .	2
.rates_base_url . . . . .	2
.send_gold_endpoint_request . . . . .	3
.send_rates_endpoint_request . . . . .	3
.send_tables_endpoint_request . . . . .	4
.tables_base_url . . . . .	4
add_json_format . . . . .	4
add_path_part . . . . .	5

create_request . . . . .	5
get_current_exchangerate . . . . .	6
get_current_exchangerate_table . . . . .	7
get_current_goldprice . . . . .	8
get_exchangerate_from . . . . .	8
get_exchangerate_from_interval . . . . .	9
get_exchangerate_tables_from_interval . . . . .	10
get_exchangerate_table_from . . . . .	11
get_goldprice_from . . . . .	12
get_goldprice_from_interval . . . . .	13
get_last_n_exchangerates . . . . .	14
get_last_n_exchangerate_tables . . . . .	15
get_last_n_goldprices . . . . .	16
get_todays_exchangerate . . . . .	17
get_todays_exchangerate_table . . . . .	18
get_todays_goldprice . . . . .	19
is_count . . . . .	20
is_date . . . . .	20
is_integer . . . . .	21
is_nbp_api_response . . . . .	21
nbp_api_base_url . . . . .	21

## Index 22

---

`.goldprice_base_url` *Returns the base url for the gold price endpoint.*

---

### Description

Returns the base url for the gold price endpoint.

### Usage

```
.goldprice_base_url()
```

---

`.rates_base_url` *Returns the base url for the rates endpoint.*

---

### Description

Returns the base url for the rates endpoint.

### Usage

```
.rates_base_url()
```

---

`.send_gold_endpoint_request`

*Sends a request and parses the gold price endpoint response.*

---

### **Description**

Sends a request and parses the gold price endpoint response.

### **Usage**

```
.send_gold_endpoint_request(request_url)
```

### **Arguments**

`request_url`      url to which the request should be sent.

### **Value**

`nbp_api_response` object with the request content.

---

`.send_rates_endpoint_request`

*Sends a request and parses the rates endpoint response.*

---

### **Description**

Sends a request and parses the rates endpoint response.

### **Usage**

```
.send_rates_endpoint_request(request_url)
```

### **Arguments**

`request_url`      url to which the request should be sent.

### **Value**

`nbp_api_response` object with the request content.

---

`.send_tables_endpoint_request`

*Sends a request and parses the tables endpoint response.*

---

**Description**

Sends a request and parses the tables endpoint response.

**Usage**

`.send_tables_endpoint_request(request_url)`

**Arguments**

`request_url`      url to which the request should be sent.

**Value**

`nbp_api_response` object with the request content.

---

`.tables_base_url`

*Returns the base url for the tables endpoint.*

---

**Description**

Returns the base url for the tables endpoint.

**Usage**

`.tables_base_url()`

---

`add_json_format`

*Adds the json formatting option to the passed url request.*

---

**Description**

Adds the json formatting option to the passed url request.

**Usage**

`add_json_format(url)`

**Arguments**

`url`                      request url to which the json format option should be added

**Value**

url with json format option added

---

add_path_part	<i>Adds a path part to the given url</i>
---------------	--

---

**Description**

Adds a path part to the given url

**Usage**

```
add_path_part(url, path_name)
```

**Arguments**

url	url to which a path part should be added
path_name	path part which should be added to the url

**Value**

url with the path part added

---

create_request	<i>Creates a request with the given path parts. The json format argument is included by default.</i>
----------------	--

---

**Description**

Creates a request with the given path parts. The json format argument is included by default.

**Usage**

```
create_request(base_url, path_parts = NULL)
```

**Arguments**

base_url	base url of the API for which a request should be created
path_parts	that should be added to the base url

**Value**

request url composed of the given base url and specified path parts

---

get\_current\_exchangerate

*Retrieves the current exchange rate for the given currency.*

---

### Description

Retrieves the current exchange rate for the given currency.

### Usage

```
get_current_exchangerate(table, currency_code)
```

### Arguments

table specifies which from which table the exchange rate should be fetched.  
currency\_code code of the currency for which the exchange rate should be fetched.

### Value

nbp\_api\_response object containing the current exchange rate.

### See Also

<https://api.nbp.pl/#kursyWalut>

Other rates: [get\\_exchangerate\\_from\(\)](#), [get\\_exchangerate\\_from\\_interval\(\)](#), [get\\_last\\_n\\_exchangerates\(\)](#), [get\\_todays\\_exchangerate\(\)](#)

### Examples

```
tryCatch(  
  {  
    ## Retrieve the current exchange rate for euros  
    response <- get_current_exchangerate("A", "EUR")  
    ## Retrieve the content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_current\_exchangerate\_table

*Retrieves the current exchange rate table.*

---

### Description

Retrieves the current exchange rate table.

### Usage

```
get_current_exchangerate_table(table)
```

### Arguments

table                specifies which table should be fetched.

### Value

nbp\_api\_response object containing the current exchange rate table.

### See Also

<https://api.nbp.pl/#kursyWalut>

Other tables: [get\\_exchangerate\\_table\\_from\(\)](#), [get\\_exchangerate\\_tables\\_from\\_interval\(\)](#), [get\\_last\\_n\\_exchangerate\\_tables\(\)](#), [get\\_todays\\_exchangerate\\_table\(\)](#)

### Examples

```
tryCatch(  
  {  
    ## Retrieve the current A exchange rate table  
    response <- get_current_exchangerate_table("A")  
    ## Retrieve the content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

get\_current\_goldprice *Retrieves the current gold price.*

---

### Description

Retrieves the current gold price.

### Usage

```
get_current_goldprice()
```

### Value

nbp\_api\_response object containing the current gold price.

### See Also

<https://api.nbp.pl/#cenyZlota>

Other goldprice: [get\\_goldprice\\_from\(\)](#), [get\\_goldprice\\_from\\_interval\(\)](#), [get\\_last\\_n\\_goldprices\(\)](#), [get\\_todays\\_goldprice\(\)](#)

### Examples

```
tryCatch(  
  {  
    ## Fetch the current gold price  
    response <- get_current_goldprice()  
    ## Retrieve the current gold price value  
    response$content$cena  
  },  
  error = function(e) message(e)  
)
```

---

get\_exchangerate\_from *Retrieves the exchange rate from a specific date.*

---

### Description

Retrieves the exchange rate from a specific date.

### Usage

```
get_exchangerate_from(table, currency_code, date)
```



**Arguments**

table	specifies which from which table the exchange rate should be fetched.
currency_code	code of the currency for which the exchange rate should be fetched.
date	date from which the exchange rate should be fetched.

**Details**

As exchange rates are not published on the weekends fetching values from a weekend date will result in a 404 error. In those cases the function returns an error with an appropriate message.

**Value**

nbp\_api\_response object containing the exchange rate from the specified date.

**See Also**

<https://api.nbp.pl/#kursyWalut>

Other rates: [get\\_current\\_exchangerate\(\)](#), [get\\_exchangerate\\_from\\_interval\(\)](#), [get\\_last\\_n\\_exchangerates\(\)](#), [get\\_todays\\_exchangerate\(\)](#)

**Examples**

```
tryCatch(  
  {  
    ## Fetch the euro exchange rate from a week ago  
    response <- get_exchangerate_from("A", "EUR", Sys.Date() - 7)  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_exchangerate\_from\_interval

*Retrieves the exchange rates from a specific interval.*

---

**Description**

Retrieves the exchange rates from a specific interval.

**Usage**

```
get_exchangerate_from_interval(table, currency_code, from, to)
```

**Arguments**

table	specifies which from which table the exchange rate should be fetched.
currency_code	code of the currency for which the exchange rate should be fetched.
from	start day of the interval.
to	end day of the interval.

**Details**

As exchange rates are not published on the weekends fetching values from an interval containing a weekend will result in a response that omits those days.

**Value**

nbp\_api\_response object containing the exchange rates from the specified interval.

**See Also**

<https://api.nbp.pl/#kursyWalut>

Other rates: [get\\_current\\_exchangerate\(\)](#), [get\\_exchangerate\\_from\(\)](#), [get\\_last\\_n\\_exchangerates\(\)](#), [get\\_todays\\_exchangerate\(\)](#)

**Examples**

```
tryCatch(  
  {  
    ## Fetch the exchange rate table from the past week  
    response <- get_exchangerate_tables_from_interval("A", Sys.Date() - 7, Sys.Date())  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_exchangerate\_tables\_from\_interval

*Retrieves the exchange rate tables from a specific interval.*

---

**Description**

Retrieves the exchange rate tables from a specific interval.

**Usage**

```
get_exchangerate_tables_from_interval(table, from, to)
```

**Arguments**

table	specifies which table should be fetched.
from	start day of the interval.
to	end day of the interval.

**Details**

As exchange rate tables are not published on the weekends fetching values from an interval containing a weekend will result in a response that omits those days.

**Value**

nbp\_api\_response object containing the exchange rates tables from the specified interval.

**See Also**

<https://api.nbp.pl/#kursyWalut>

Other tables: [get\\_current\\_exchangerate\\_table\(\)](#), [get\\_exchangerate\\_table\\_from\(\)](#), [get\\_last\\_n\\_exchangerate\\_tables\(\)](#), [get\\_todays\\_exchangerate\\_table\(\)](#)

**Examples**

```
tryCatch(  
  {  
    ## Fetch the exchange rate table from the past week  
    response <- get_exchangerate_tables_from_interval("A", Sys.Date() - 7, Sys.Date())  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_exchangerate\_table\_from

*Retrieves the exchange rate table from a specific date.*

---

**Description**

Retrieves the exchange rate table from a specific date.

**Usage**

```
get_exchangerate_table_from(table, date)
```

**Arguments**

table specifies which table should be fetched.  
date date from which the exchange rate table should be fetched.

**Details**

As exchange rate tables are not published on the weekends fetching values from a weekend date will result in a 404 error. In those cases the function returns an error with an appropriate message.

**Value**

nbp\_api\_response object containing the exchange rate table from the specified date.

**See Also**

<https://api.nbp.pl/#kursyWalut>

Other tables: [get\\_current\\_exchangerate\\_table\(\)](#), [get\\_exchangerate\\_tables\\_from\\_interval\(\)](#), [get\\_last\\_n\\_exchangerate\\_tables\(\)](#), [get\\_todays\\_exchangerate\\_table\(\)](#)

**Examples**

```
tryCatch(  
  {  
    ## Fetch the A exchange rate table from a week ago  
    response <- get_exchangerate_table_from("A", Sys.Date() - 7)  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_goldprice\_from *Retrieves the gold price from a specific date.*

---

**Description**

Retrieves the gold price from a specific date.

**Usage**

```
get_goldprice_from(date)
```

**Arguments**

date date from which the gold price should be fetched.

**Details**

As gold prices are not published on the weekends fetching values from a weekend date will result in a 404 error. In those cases the function returns an error with an appropriate message.

**Value**

nbp\_api\_response object containing the gold price from the specified date.

**See Also**

<https://api.nbp.pl/#cenyZlota>

Other goldprice: [get\\_current\\_goldprice\(\)](#), [get\\_goldprice\\_from\\_interval\(\)](#), [get\\_last\\_n\\_goldprices\(\)](#), [get\\_todays\\_goldprice\(\)](#)

**Examples**

```
tryCatch(  
  {  
    ## Fetch the gold price from a week ago  
    response <- get_goldprice_from(Sys.Date() - 7)  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_goldprice\_from\_interval

*Retrieves the gold prices from a specific interval.*

---

**Description**

Retrieves the gold prices from a specific interval.

**Usage**

```
get_goldprice_from_interval(from, to)
```

**Arguments**

from	start day of the interval.
to	end day of the interval.

**Details**

As gold prices are not published on the weekends fetching values from an interval containing a weekend will result in a response that omits those days.

**Value**

nbp\_api\_response object containing the gold prices from the specified interval.

**See Also**

<https://api.nbp.pl/#cenyZlota>

Other goldprice: `get_current_goldprice()`, `get_goldprice_from()`, `get_last_n_goldprices()`, `get_todays_goldprice()`

**Examples**

```
tryCatch(  
  {  
    ## Fetch the gold prices from the past week  
    response <- get_goldprice_from_interval(Sys.Date() - 7, Sys.Date())  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_last\_n\_exchangerates

*Retrieves the last n exchange rates.*

---

**Description**

Retrieves the last n exchange rates.

**Usage**

```
get_last_n_exchangerates(table, currency_code, n)
```

**Arguments**

table specifies which from which table the exchange rate should be fetched.

currency\_code code of the currency for which the exchange rate should be fetched.

n number of exchange rates to retrieve.

**Value**

nbp\_api\_response object containing the last n exchange rates.

**See Also**

<https://api.nbp.pl/#kursyWalut>

Other rates: [get\\_current\\_exchangerate\(\)](#), [get\\_exchangerate\\_from\(\)](#), [get\\_exchangerate\\_from\\_interval\(\)](#), [get\\_todays\\_exchangerate\(\)](#)

**Examples**

```
tryCatch(  
  {  
    ## Fetch the last 3 exchange rates for euros  
    response <- get_last_n_exchangerates("A", "EUR", 3)  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_last\_n\_exchangerate\_tables

*Retrieves the last n exchange rate tables.*

---

**Description**

Retrieves the last n exchange rate tables.

**Usage**

```
get_last_n_exchangerate_tables(table, n)
```

**Arguments**

table            specifies which table should be fetched.  
n                number of exchange rate tables to retrieve.

**Value**

nbp\_api\_response object containing the last n exchange rate tables.

**See Also**

<https://api.nbp.pl/#kursyWalut>

Other tables: [get\\_current\\_exchangerate\\_table\(\)](#), [get\\_exchangerate\\_table\\_from\(\)](#), [get\\_exchangerate\\_tables\\_fr](#), [get\\_todays\\_exchangerate\\_table\(\)](#)

## Examples

```
tryCatch(  
  {  
    ## Fetch the last 3 A exchange rate tables  
    response <- get_last_n_exchangerate_tables("A", 3)  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_last\_n\_goldprices *Retrieves the last n gold prices.*

---

## Description

Retrieves the last n gold prices.

## Usage

```
get_last_n_goldprices(n)
```

## Arguments

n                    number of gold prices to retrieve.

## Value

nbp\_api\_response object containing the last n gold prices.

## See Also

<https://api.nbp.pl/#cenyZlota>

Other goldprice: [get\\_current\\_goldprice\(\)](#), [get\\_goldprice\\_from\(\)](#), [get\\_goldprice\\_from\\_interval\(\)](#), [get\\_todays\\_goldprice\(\)](#)

## Examples

```
tryCatch(  
  {  
    ## Fetch the last 3 gold price values  
    response <- get_last_n_goldprices(3)  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```



---

`get_todays_exchangerate`*Retrieves the exchange rate that was published today.*

---

### Description

Retrieves the exchange rate that was published today.

### Usage

```
get_todays_exchangerate(table, currency_code)
```

### Arguments

`table` specifies which from which table the exchange rate should be fetched.  
`currency_code` code of the currency for which the exchange rate should be fetched.

### Details

If today's data is not available the API will return a 404 Not found error. In that case the function will return an error with an appropriate message.

### Value

`nbp_api_response` object containing today's exchange rate.

### See Also

<https://api.nbp.pl/#kursyWalut>

Other rates: `get_current_exchangerate()`, `get_exchangerate_from()`, `get_exchangerate_from_interval()`, `get_last_n_exchangerates()`

### Examples

```
tryCatch(  
  {  
    ## Fetch todays A exchange rate table  
    response <- get_todays_exchangerate("A", "EUR")  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

`get_todays_exchangerate_table`*Retrieves the exchange rate table that was published today.*

---

### Description

Retrieves the exchange rate table that was published today.

### Usage

```
get_todays_exchangerate_table(table)
```

### Arguments

`table` specifies which table should be fetched.

### Details

If today's data is not available the API will return a 404 Not found error. In that case the function will return an error with an appropriate message.

### Value

`nbp_api_response` object containing today's exchange rate table.

### See Also

<https://api.nbp.pl/#kursyWalut>

Other tables: [get\\_current\\_exchangerate\\_table\(\)](#), [get\\_exchangerate\\_table\\_from\(\)](#), [get\\_exchangerate\\_tables\\_from\(\)](#), [get\\_last\\_n\\_exchangerate\\_tables\(\)](#)

### Examples

```
tryCatch(  
  {  
    ## Fetch todays A exchange rate table  
    response <- get_todays_exchangerate_table("A")  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

get\_todays\_goldprice *Retrieves the gold price that was published today.*

---

### Description

Retrieves the gold price that was published today.

### Usage

```
get_todays_goldprice()
```

### Details

If today's data is not available the API will return a 404 Not found error. In that case the function will return an error with an appropriate message.

### Value

nbp\_api\_response object containing today's gold price.

### See Also

<https://api.nbp.pl/#cenyZlota>

Other goldprice: [get\\_current\\_goldprice\(\)](#), [get\\_goldprice\\_from\(\)](#), [get\\_goldprice\\_from\\_interval\(\)](#), [get\\_last\\_n\\_goldprices\(\)](#)

### Examples

```
tryCatch(  
  {  
    ## Fetch todays gold price  
    response <- get_todays_goldprice()  
    ## Preview response content  
    response$content  
  },  
  error = function(e) message(e)  
)
```

---

is_count	<i>Checks if an object is a positive integer.</i>
----------	---

---

**Description**

Checks if an object is a positive integer.

**Usage**

```
is_count(x)
```

**Arguments**

x                    object to be tested.

**Value**

TRUE or FALSE depending on whether its argument is a positive integer or not.

---

is_date	<i>Checks if an object is a date object.</i>
---------	--

---

**Description**

Checks if an object is a date object.

**Usage**

```
is_date(x)
```

**Arguments**

x                    object to be tested.

**Value**

TRUE or FALSE depending on whether its arguments is a date object or not.

---

is_integer	<i>Checks if an object is an integer.</i>
------------	---

---

**Description**

Checks if an object is an integer.

**Usage**

```
is_integer(x)
```

**Arguments**

x                    object to be tested.

**Value**

TRUE or FALSE depending on whether its argument is an integer or not.

---

is_nbp_api_response	<i>Checks whether the given object is of the class nbp_api_response.</i>
---------------------	--

---

**Description**

Checks whether the given object is of the class nbp\_api\_response.

**Usage**

```
is_nbp_api_response(x)
```

**Arguments**

x                    object to test if it is of the class nbp\_api\_response

**Value**

TRUE if the object is of the class nbp\_api\_response

---

nbp_api_base_url	<i>Returns the base url of the nbp api.</i>
------------------	---

---

**Description**

Returns the base url of the nbp api.

**Usage**

```
nbp_api_base_url()
```

# Index

- \* **goldprice**
  - get\_current\_goldprice, 8
  - get\_goldprice\_from, 12
  - get\_goldprice\_from\_interval, 13
  - get\_last\_n\_goldprices, 16
  - get\_todays\_goldprice, 19
- \* **rates**
  - get\_current\_exchangerate, 6
  - get\_exchangerate\_from, 8
  - get\_exchangerate\_from\_interval, 9
  - get\_last\_n\_exchangerates, 14
  - get\_todays\_exchangerate, 17
- \* **tables**
  - get\_current\_exchangerate\_table, 7
  - get\_exchangerate\_table\_from, 11
  - get\_exchangerate\_tables\_from\_interval, 10
  - get\_last\_n\_exchangerate\_tables, 15
  - get\_todays\_exchangerate\_table, 18
- .goldprice\_base\_url, 2
- .rates\_base\_url, 2
- .send\_gold\_endpoint\_request, 3
- .send\_rates\_endpoint\_request, 3
- .send\_tables\_endpoint\_request, 4
- .tables\_base\_url, 4
  
- add\_json\_format, 4
- add\_path\_part, 5
  
- create\_request, 5
  
- get\_current\_exchangerate, 6, 9, 10, 15, 17
- get\_current\_exchangerate\_table, 7, 11, 12, 15, 18
- get\_current\_goldprice, 8, 13, 14, 16, 19
- get\_exchangerate\_from, 6, 8, 10, 15, 17
- get\_exchangerate\_from\_interval, 6, 9, 9, 15, 17
- get\_exchangerate\_table\_from, 7, 11, 11, 15, 18
- get\_exchangerate\_tables\_from\_interval, 7, 10, 12, 15, 18
- get\_goldprice\_from, 8, 12, 14, 16, 19
- get\_goldprice\_from\_interval, 8, 13, 13, 16, 19
- get\_last\_n\_exchangerate\_tables, 7, 11, 12, 15, 18
- get\_last\_n\_exchangerates, 6, 9, 10, 14, 17
- get\_last\_n\_goldprices, 8, 13, 14, 16, 19
- get\_todays\_exchangerate, 6, 9, 10, 15, 17
- get\_todays\_exchangerate\_table, 7, 11, 12, 15, 18
- get\_todays\_goldprice, 8, 13, 14, 16, 19
  
- is\_count, 20
- is\_date, 20
- is\_integer, 21
- is\_nbp\_api\_response, 21
  
- nbp\_api\_base\_url, 21